



HDPE Conduit for underground cable protection



Kanaflex®
BRAZIL



Nominal Diameter	SDR Schedule	OD Outside Diameter		Wall Thickness		Nominal Diameter	SDR Schedule	OD Outside Diameter		Wall Thickness	
		Inches	Tolerance	Inches	Tolerance			Inches	Tolerance	Inches	Tolerance
1/2"	SDR 9	0,84	± 0,004	0,093	+0,020	3"	SDR 9	3,5	± 0,018	0,389	+0,047
	SDR 11	0,84	± 0,004	0,076	+0,020		SDR 11	3,5	± 0,018	0,318	+0,038
	SDR 13.5	0,84	± 0,004	0,062	+0,020		SDR 13.5	3,5	± 0,018	0,259	+0,031
	DR 15.5	0,84	± 0,004	0,062	+0,020		DR 15.5	3,5	± 0,018	0,226	+0,027
	Schedule 40	0,84	± 0,004	0,109	+0,020		Schedule 40	3,5	± 0,018	0,216	+0,026
	Schedule 80	0,84	± 0,004	0,147	+0,020		Schedule 80	3,5	± 0,018	0,300	+0,036
3/4"	SDR 9	1,05	± 0,005	0,117	+0,020	4"	SDR 9	4,5	± 0,023	0,500	+0,060
	SDR 11	1,05	± 0,005	0,095	+0,020		SDR 11	4,5	± 0,023	0,409	+0,049
	SDR 13.5	1,05	± 0,005	0,078	+0,020		SDR 13.5	4,5	± 0,023	0,333	+0,040
	DR 15.5	1,05	± 0,005	0,068	+0,020		DR 15.5	4,5	± 0,023	0,290	+0,035
	Schedule 40	1,05	± 0,005	0,113	+0,020		Schedule 40	4,5	± 0,023	0,237	+0,028
	Schedule 80	1,05	± 0,005	0,154	+0,020		Schedule 80	4,5	± 0,023	0,337	+0,040
1"	SDR 9	1,315	± 0,007	0,146	+0,020	5"	SDR 9	5,563	± 0,028	0,618	+0,074
	SDR 11	1,315	± 0,007	0,120	+0,020		SDR 11	5,563	± 0,028	0,506	+0,061
	SDR 13.5	1,315	± 0,007	0,097	+0,020		SDR 13.5	5,563	± 0,028	0,412	+0,049
	DR 15.5	1,315	± 0,007	0,084	+0,020		DR 15.5	5,563	± 0,028	0,359	+0,043
	Schedule 40	1,315	± 0,007	0,133	+0,020		Schedule 40	5,563	± 0,028	0,258	+0,031
	Schedule 80	1,315	± 0,007	0,179	+0,021		Schedule 80	5,563	± 0,028	0,375	+0,045
1.1/4"	SDR 9	1,66	± 0,008	0,184	+0,022	6"	SDR 9	6,625	± 0,033	0,736	+0,088
	SDR 11	1,66	± 0,008	0,151	+0,020		SDR 11	6,625	± 0,033	0,602	+0,072
	SDR 13.5	1,66	± 0,008	0,123	+0,020		SDR 13.5	6,625	± 0,033	0,491	+0,059
	DR 15.5	1,66	± 0,008	0,107	+0,020		DR 15.5	6,625	± 0,033	0,427	+0,051
	Schedule 40	1,66	± 0,008	0,140	+0,020		Schedule 40	6,625	± 0,033	0,280	+0,034
	Schedule 80	1,66	± 0,008	0,191	+0,023		Schedule 80	6,625	± 0,033	0,432	+0,050
1.1/2"	SDR 9	1,9	± 0,010	0,211	+0,025	8"	SDR 9	8,625	± 0,043	0,958	+0,115
	SDR 11	1,9	± 0,010	0,173	+0,021		SDR 11	8,625	± 0,043	0,784	+0,094
	SDR 13.5	1,9	± 0,010	0,141	+0,020		SDR 13.5	8,625	± 0,043	0,639	+0,077
	DR 15.5	1,9	± 0,010	0,123	+0,020		DR 15.5	8,625	± 0,043	---	---
	Schedule 40	1,9	± 0,010	0,145	+0,020		Schedule 40	8,625	± 0,043	---	---
	Schedule 80	1,9	± 0,010	0,200	+0,024		Schedule 80	8,625	± 0,043	---	---
2"	SDR 9	2,375	± 0,012	0,264	+0,032	10"	SDR 9	10,75	± 0,054	1,194	+0,143
	SDR 11	2,375	± 0,012	0,216	+0,026		SDR 11	10,75	± 0,054	0,977	+0,117
	SDR 13.5	2,375	± 0,012	0,176	+0,020		SDR 13.5	10,75	± 0,054	0,796	+0,096
	DR 15.5	2,375	± 0,012	0,153	+0,020		DR 15.5	10,75	± 0,054	---	---
	Schedule 40	2,375	± 0,012	0,154	+0,020		Schedule 40	10,75	± 0,054	---	---
	Schedule 80	2,375	± 0,012	0,218	+0,026		Schedule 80	10,75	± 0,054	---	---
2.1/2"	SDR 9	2,875	± 0,014	0,319	+0,038	12"	SDR 9	12,75	± 0,064	1,417	+0,170
	SDR 11	2,875	± 0,014	0,261	+0,031		SDR 11	12,75	± 0,064	1,159	+0,139
	SDR 13.5	2,875	± 0,014	0,213	+0,020		SDR 13.5	12,75	± 0,064	0,944	+0,113
	DR 15.5	2,875	± 0,014	0,185	+0,022		DR 15.5	12,75	± 0,064	---	---
	Schedule 40	2,875	± 0,014	0,203	+0,024		Schedule 40	12,75	± 0,064	---	---
	Schedule 80	2,875	± 0,014	0,276	+0,033		Schedule 80	12,75	± 0,064	---	---

Protecting underground cables.



Main Features

- Super resistant to impact, compression and traction
- Ideal for installation using the non-destructive method (Trenchless)
- Allows cables to be inflated over long distances

Optilex is a conduit made of HDPE (high density polyethylene) by extrusion process, with a smooth outside surface and longitudinal ribs on the inside.

It can be supplied in several colors, with or without a stripe.

The main application is for cable protection in underground installations of Optical Fiber, Telecommunication and Power cables.

The raw material used to produce Optilex is HDPE - High Density Polyethylene, with added antioxidants, UV stabilizers and pigments, which provides resistance to UV light, chemical products and environmental stress crack (ESCR).

Optilex conduits up to 2" OD are supplied in 4,922' to 6,562' lengths* in steel reels with the following dimensions:

- Outside diameter: 100"
- Inside diameter: 33"
- Width: 47"

Optilex conduits from 2 ½ " OD to 12" OD are supplied in rolls of 164' and 328' lengths*.

All Optilex conduit specifications meet or exceed **ASTM F2160 standard**.

* Custom lengths are available to conform with client and project specifications. Kanaflex offers diameters up to 12" for special projects.

Consult us for detailed specifications.

Kanaflex®
Infrastructure Division

São Paulo Unit



Ceará Unit



Kanaflex's manufacturing park is modern and capable of meeting the greatest demands of the most varied segments, providing reliable supply within the established deadlines.

Kanaflex®
BRAZIL

Rua José Semião Rodrigues Agostinho, 282

Embu das Artes - SP - Brazil - 06833-905

Fone: (55 11) 4758-2100 www.kanaflex.com.br douglas@kanaflex.com.br

ISO 9001

Consult us for more information.